TECHNICAL PARAMETERS

SL500U		
Engine Model	XY192MR	
Engine Type	Four-Stroke, Single Cylinder, Water Cooling, Balance shaft Engine	
Displacement	498.6	(cc)
Bore & Stroke	92& 75	(mm)
Compression Ratio	10.2:1	
Fuel System	Electronic Fuel Injection (EFI)	
Ignition	Electronic Control Unit	(ECU)
Transmission	Automatic L-H-N-R	
Drive Train	Shaft Drive; 2WD-4WD; Front and rear differential with lock	
Cooling	Liquid	
Nominal Power	22kW / 6000	(rpm)
Max Torque	40Nm / 4800	(rpm)
Fuel Tank Capacity	30	(L)
Battery	12V 32Ah	
Maximum Speed	85	(km/h)
Overall Length	120.9	(in)
Overall Width	63.9	(in)
Overall Height	81.1	(in)
Ground Clearance	9	(in)
Front Tire	26x9-14	
Rear Tire	26x11-14	
Wheel Base	74	(in)
Dry Weight	669	(kg)
Bed Capacity	551	(lbs)
Bed Dimension	48(W) x 36.4 (L)	(in)
Winch	12V 3500	(lbs)
Front Suspension	Independent Double A-Arm	
Rear Suspension	Independent Double A-Arm	
Front Brake	Ventilated Hydraulic Disc	
Rear Brake	Ventilated Hydraulic Disc	