SLE 20

Overall Length: 3250 (mm)
Overall Width: 1100 (mm)
Overall Height: 2230 (mm)
Track Width: 180 (mm)
Track Length: 1150 (mm)
Body Width: 1018 (mm)

TECHNICAL PARAMETERS

THE FEATURE		
Engine Brand	Kubota D722	
Rated Power	10.2	(kw)
Cab	Sunshade Canopy	
Pedrail	Rubber Track	
Accessories	Toolbox	
SPECIFICATION		
Overall weight	0.95	(t)
Digging Bucket Capacity	0.02	(m^3)
Bucket Width	350	(mm)
Traveling Motor	Ruili/Lipton	
Travel Speed	0-1.8	(km/h)
Swing Motor	Ruili/Lipton	
Swing Speed	8r/min	(rpm)
Hydraulic system	Gear pump: Tianjin walking Integrated multi way valve: Taiheng	
Body Swing Radius	700	(mm)
Body Swing Angel	360	
Boom Swing Angel (L/R)	45°/45°	
Max. Grade Ability	15°	(%)
Fuel Tank	11	(L)
Hydraulic Oil Tank	11	(L)
WORKING RANGE		
Max. Digging Radius	2740	(mm)
Max Digging Depth	1570	(mm)
Max. Digging Height	2967	(mm)
Max. Unloading Height	2192	(mm)
Min. Swing Radius	716	(mm)
Max. Digging Depth Of Dozer Blade	156	(mm)
Max. Lifting Height Of Dozer Blade	150	(mm)

OPTION

Engine, Cab, Track, Telescopic Chassis, Air Conditioning, High And Low Speed Motors

Sophisticated Instruments

Precision Bucket

Powerful & Reliable