SLE 32

Overall Length: 3400 (mm)
Overall Width: 1320 (mm)
Overall Height: 2380 (mm)
Track Width: 230 (mm)
Track Length: 1800 (mm)
Body Width: 1310 (mm)

TECHNICAL PARAMETERS

THE FEATURE		
Engine Brand	Kubota D902	
Rated Power	11.8	(kw)
Side Swing	Standard Side Swing	
Cab	Driving Cab	
Pedrail	Rubber Track	
Accessories	Toolbox	
SPECIFICATION		
Overall weight	1.9	(t)
Digging Bucket Capacity	0.03	(m^3)
Bucket Width	500	(mm)
Traveling Motor	Ruili/Lipton	
Travel Speed	0-1.8	(km/h)
Swing Motor	Ruili/Lipton	
Swing Speed	10r/min	(rpm)
Hydraulic system	Piston pump: Taifeng Load sensitive valve: Taifeng	
Body Swing Radius	894	(mm)
Body Swing Angel	360	
Boom Swing Angel (L/R)	45°/45°	
Max. Grade Ability	15°	(%)
Fuel Tank	15	(L)
Hydraulic Oil Tank	22	(L)
WORKING RANGE		
Max. Digging Radius	3580	(mm)
Max Digging Depth	1980	(mm)
Max. Digging Height	2750	(mm)
Max. Unloading Height	2000	(mm)
Min. Swing Radius	1865	(mm)
Max. Digging Depth Of Dozer Blade	250	(mm)
Max. Lifting Height Of Dozer Blade	170	(mm)

OPTION

Engine, Cab, Track, Telescopic Chassis, Air Conditioning, High And Low Speed Motors

Clearly Display



Sophisticated Instruments



Powerful & Reliable